

Safety Data Sheet
acc. to OSHA HCS

Printing date 05/23/2022

Reviewed on 05/23/2022

1 Identification

- **Product identifier**
- **Trade name: Hardener**
- **Article number: Series 700-HDI**
- **Application of the substance / the mixture** Additive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
DECO TEChnology Group Inc.
PRINTCOLOR SCREEN AG
TEL (714) 639-3326
FAX (714) 639-2261
- **Information department:** Product safety department
- **Emergency telephone number:** 800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 3

H226 Flammable liquid and vapor.



GHS08 Health hazard

Sensitization - Respiratory 1

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carcinogenicity 2

H351 Suspected of causing cancer.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Aromatic polyisocyanate
xylene

(Contd. on page 2)

Trade name: Hardener

(Contd. of page 1)

m-tolylidene diisocyanate

· **Hazard statements**

- Flammable liquid and vapor.
- Harmful if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- May cause an allergic skin reaction.
- Suspected of causing cancer.
- May be fatal if swallowed and enters airways.

· **Precautionary statements**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Wash thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves/protective clothing/eye protection/face protection.
- [In case of inadequate ventilation] wear respiratory protection.
- If swallowed: Immediately call a poison center/doctor.
- Do NOT induce vomiting.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- Specific treatment (see on this label).
- Call a poison center/doctor if you feel unwell.
- Take off contaminated clothing and wash it before reuse.
- If skin irritation or rash occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- If experiencing respiratory symptoms: Call a poison center/doctor.
- Wash contaminated clothing before reuse.
- In case of fire: Use CO₂, powder or water spray to extinguish.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 2
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2
Fire = 2
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

(Contd. on page 3)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 53317-61-6	Aromatic polyisocyanate	50-100%
CAS: 1330-20-7	xylene	10-25%
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	≥10-<20%
CAS: 26471-62-5	m-tolyldiene diisocyanate	≥0.1-<0.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 3)

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
CAS: 26471-62-5	m-tolyldiene diisocyanate	0.02 ppm

· **PAC-2:**

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
CAS: 26471-62-5	m-tolyldiene diisocyanate	0.083 ppm

· **PAC-3:**

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
CAS: 26471-62-5	m-tolyldiene diisocyanate	0.51 ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Prevent formation of aerosols.
Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.
Use only in well ventilated areas.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

· **Storage class:** 3

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

(Contd. on page 5)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 4)

CAS: 26471-62-5 m-tolyldene diisocyanate

PEL	Ceiling limit value: 0.14 mg/m ³ , 0.02 ppm
REL	LFC
TLV	Short-term value: (0.14) NIC-0.021* mg/m ³ , (0.02) NIC-0.003* ppm Long-term value: (0.036) NIC-0.007* mg/m ³ , (0.005) NIC-0.001* ppm *(IFV) SEN; NIC-Skin; A3

Ingredients with biological limit values:

CAS: 1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

Breathing equipment: Not necessary if room is well-ventilated.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Safety glasses

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid

(Contd. on page 6)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 5)

· Color:	Yellowish
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	145 °C (293 °F)
· Flash point:	41 °C (105.8 °F) (Abel Pensky)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
· Vapor pressure at 20 °C (68 °F):	3.4 hPa (2.6 mm Hg)
· Density at 20 °C (68 °F):	1.15 g/cm ³ (9.6 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	600 s (DIN 53211/4)
· Solvent separation test	
VOC content:	32.70 %
	376.1 g/l / 3.14 lb/gal
VOC (EC)	32.70 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

CAS: 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 1330-20-7	xylene	3
CAS: 26471-62-5	m-tolyldiene diisocyanate	2B

· **NTP (National Toxicology Program)**

CAS: 26471-62-5	m-tolyldiene diisocyanate	R
-----------------	---------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Printing date 05/23/2022




Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	UN1210
· DOT, ADR, IMDG, IATA	UN1210
· UN proper shipping name	Printing ink related material
· DOT	1210 PRINTING INK RELATED MATERIAL
· ADR	PRINTING INK RELATED MATERIAL
· IMDG, IATA	PRINTING INK RELATED MATERIAL
· Transport hazard class(es)	
· DOT	
	
· Class	3 Flammable liquids
· Label	3
· ADR, IATA	
	
· Class	3 Flammable liquids
· Label	3
· IMDG	
	
· Class	3 Flammable liquids
· Label	Not restricted good <450l according to IMDG 2.3.2.5 3
· Packing group	III
· DOT, ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E,S-D
· Stowage Category	E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

(Contd. on page 9)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 8)

· **Transport/Additional information:**· **ADR**· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1210 PRINTING INK RELATED MATERIAL, 3, III

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 26471-62-5 | m-tolyldiene diisocyanate

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**· **Chemicals known to cause cancer:**

CAS: 26471-62-5 | m-tolyldiene diisocyanate

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogeny categories**· **EPA (Environmental Protection Agency)**

CAS: 1330-20-7 | xylene

I

· **TLV (Threshold Limit Value)**

CAS: 1330-20-7 | xylene

A4

CAS: 26471-62-5 | m-tolyldiene diisocyanate

(A4)

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

US

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 9)

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Aromatic polyisocyanate
xylene
m-tolylidene diisocyanate

· **Hazard statements**

Flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.
May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Call a poison center/doctor if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
In case of fire: Use CO₂, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 11)

Printing date 05/23/2022

Reviewed on 05/23/2022

Trade name: Hardener

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:**

msds@teca-print.com

hse@printcolor.ch

· **Date of preparation / last revision** 05/23/2022 / 6

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Respiratory 1: Respiratory sensitisation – Category 1

Sensitization - Skin 1: Skin sensitisation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1