

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/08/2019

Reviewed on 01/08/2019

1 Identification

- **Product identifier**
- **Trade name: ST-White**
- **Article number: Series 747-00**
- **Application of the substance / the mixture** Printing inks
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
DECO TEChnology Group Inc.
PRINTCOLOR SCREEN AG
TEL (714) 639-3326
FAX (714) 639-2261
- **Information department:** Product safety department
- **Emergency telephone number:** 800-535-5053

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

- Carc. 2 H351 Suspected of causing cancer.
- Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Warning

- **Hazard-determining components of labeling:**

titanium dioxide
2-hydroxyethyl methacrylate
Oligo[2-hydroxy-2-methyl-1-[4-(1-methylvinyl)phenyl]propanone]
Dipentaerythritolhexaacrylat
2-phenoxyethyl acrylate
tripropylene glycol diacrylate
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid
glycerol, propoxylated, esters with acrylic acid

(Contd. on page 2)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 1)

hexamethylene diacrylate

· **Hazard statements**

- Combustible liquid.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause an allergic skin reaction.
- Suspected of causing cancer.
- Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep container tightly closed.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing vapours.
- Wash thoroughly after handling.
- Contaminated work clothing must not be allowed out of the workplace.
- Wear protective gloves / eye protection.
- Use personal protective equipment as required.
- If on skin: Wash with plenty of water.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- Specific treatment (see on this label).
- Take off contaminated clothing and wash it before reuse.
- If skin irritation or rash occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Wash contaminated clothing before reuse.
- In case of fire: Use for extinction: CO2, powder or water spray.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 2
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2
FIRE 2 Fire = 2
REACTIVITY 0 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 13463-67-7	titanium dioxide	25-50%
CAS: 123-86-4	n-butyl acetate	2.5-10%

(Contd. on page 3)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 2)

CAS: 868-77-9	2-hydroxyethyl methacrylate	2.5-10%
CAS: 29570-58-9	Dipentaerythritolhexaacrylat	2.5-10%
CAS: 163702-01-0	Oligo[2-hydroxy-2-methyl-1-[4-(1-methylvinyl)phenyl]propanone]	2.5-10%
CAS: 327622-75-3	Fatty acids, C18-unsatd., dimers, polymers with acrylic acid and 1,3,5-tris(2-hydroxyethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	2.5-10%
CAS: 7727-43-7	barium sulphate, natural	1-2.5%
CAS: 75980-60-8	diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	1-2.5%
CAS: 7473-98-5	2-hydroxy-2-methylpropiophenone	1-2.5%
CAS: 24599-21-1	2-(phosphonooxy)ethyl methacrylate	1-2.5%
CAS: 32435-46-4	bis(methacryloyloxyethyl) hydrogen phosphate	1-2.5%
CAS: 954-16-5	2,4,6-trimethylbenzophenone	1-2.5%
CAS: 48145-04-6	2-phenoxyethyl acrylate	1-2.5%
CAS: 157811-87-5	Siloxanes and silicones, di-Me, hydrogen-terminated, reaction products with pentaerythritol tetraacrylate	1-2.5%
CAS: 63225-53-6	2-[[[(butylamino)carbonyl]oxy]ethyl acrylate	1-2.5%
CAS: 42978-66-5	tripropylene glycol diacrylate	<0.5%
CAS: 55818-57-0	4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid	<0.5%
CAS: 52408-84-1	glycerol, propoxylated, esters with acrylic acid	<0.5%
CAS: 13048-33-4	hexamethylene diacrylate	<0.5%

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:** No special measures required.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Trade name: ST-White

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

• **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

• **Protective Action Criteria for Chemicals**

• **PAC-1:**

CAS: 13463-67-7	titanium dioxide	30 mg/m ³
CAS: 123-86-4	n-butyl acetate	5 ppm
CAS: 868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m ³
CAS: 7727-43-7	barium sulphate, natural	15 mg/m ³
CAS: 9002-84-0	Polytetrafluoroethylene	12 mg/m ³
CAS: 7631-86-9	silicon dioxide, chemically prepared	18 mg/m ³
CAS: 13048-33-4	hexamethylene diacrylate	3 mg/m ³
CAS: 1344-28-1	aluminium oxide	15 mg/m ³
CAS: 79-10-7	acrylic acid	1.5 ppm
CAS: 97-88-1	n-butyl methacrylate	19 mg/m ³
CAS: 150-76-5	mequinol	15 mg/m ³
CAS: 80-62-6	methyl methacrylate	17 ppm

• **PAC-2:**

CAS: 13463-67-7	titanium dioxide	330 mg/m ³
CAS: 123-86-4	n-butyl acetate	200 ppm
CAS: 868-77-9	2-hydroxyethyl methacrylate	21 mg/m ³
CAS: 7727-43-7	barium sulphate, natural	170 mg/m ³
CAS: 9002-84-0	Polytetrafluoroethylene	130 mg/m ³
CAS: 7631-86-9	silicon dioxide, chemically prepared	740 mg/m ³
CAS: 13048-33-4	hexamethylene diacrylate	170 mg/m ³
CAS: 1344-28-1	aluminium oxide	170 mg/m ³
CAS: 79-10-7	acrylic acid	46 ppm
CAS: 97-88-1	n-butyl methacrylate	210 mg/m ³
CAS: 150-76-5	mequinol	49 mg/m ³
CAS: 80-62-6	methyl methacrylate	120 ppm

• **PAC-3:**

CAS: 13463-67-7	titanium dioxide	2,000 mg/m ³
CAS: 123-86-4	n-butyl acetate	3000* ppm
CAS: 868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m ³
CAS: 7727-43-7	barium sulphate, natural	990 mg/m ³
CAS: 9002-84-0	Polytetrafluoroethylene	790 mg/m ³
CAS: 7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m ³
CAS: 13048-33-4	hexamethylene diacrylate	990 mg/m ³
CAS: 1344-28-1	aluminium oxide	990 mg/m ³
CAS: 79-10-7	acrylic acid	180 ppm
CAS: 97-88-1	n-butyl methacrylate	1,300 mg/m ³
CAS: 150-76-5	mequinol	320 mg/m ³

(Contd. on page 5)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

CAS: 80-62-6

methyl methacrylate

(Contd. of page 4)

570 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

CAS: 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

CAS: 7727-43-7 barium sulphate, natural

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 5* mg/m ³ *inhalable fraction; E

CAS: 13048-33-4 hexamethylene diacrylate

WEEL	Long-term value: 1 mg/m ³ DSEN
------	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 5)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: > 100 °C (>212 °F)

· **Flash point:** 65 °C (149 °F) (Abel Pensky)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 370 °C (698 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower: Not determined.
Upper: Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 1.52 g/cm³ (12.68 lbs/gal)

· **Relative density** Not determined.

(Contd. on page 7)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 6)

- **Vapor density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic at 20 °C (68 °F):** 4000 mPas
 - Kinematic:** Not determined.
 - VOC content:** 8.0 %
- **Other information** 170.3 g/l / 1.42 lb/gal
No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

CAS: 13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 13463-67-7	titanium dioxide	2B
CAS: 9002-84-0	Polytetrafluoroethylene	3
CAS: 7631-86-9	silicon dioxide, chemically prepared	3
CAS: 128-37-0	Butylated hydroxytoluene	3
CAS: 79-10-7	acrylic acid	3
CAS: 80-62-6	methyl methacrylate	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 8)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 7)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------|-----------------------------|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN | |
| · Class | Void |
| · IMDG, IATA | |
| · Class | Void
Not restricted good |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Void |
| · Environmental hazards: | |
| · Marine pollutant: | No |

(Contd. on page 9)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 8)

- | | |
|--|-----------------|
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 7727-43-7	barium sulphate, natural
CAS: 1344-28-1	aluminium oxide
CAS: 79-10-7	acrylic acid
CAS: 80-62-6	methyl methacrylate

· **TSCA (Toxic Substances Control Act):**

CAS: 13463-67-7	titanium dioxide
CAS: 123-86-4	n-butyl acetate
CAS: 868-77-9	2-hydroxyethyl methacrylate
CAS: 60506-81-2	Dipentaerythritol Pentaacrylate Esters
CAS: 29570-58-9	Dipentaerythritolhexaacrylat
CAS: 7727-43-7	barium sulphate, natural
CAS: 9002-84-0	Polytetrafluoroethylene
CAS: 75980-60-8	diphenyl(2,4,6- trimethylbenzoyl)phosphine oxide
CAS: 7473-98-5	2-hydroxy-2-methylpropiophenone
CAS: 24599-21-1	2-(phosphonooxy)ethyl methacrylate
CAS: 32435-46-4	bis(methacryloyloxyethyl) hydrogen phosphate
CAS: 954-16-5	2,4,6-trimethylbenzophenone
CAS: 48145-04-6	2-phenoxyethyl acrylate
CAS: 157811-87-5	Siloxanes and silicones, di-Me, hydrogen-terminated, reaction products with pentaerythritol tetraacrylate
CAS: 63225-53-6	2-[[[(butylamino)carbonyl]oxy]ethyl acrylate
CAS: 7631-86-9	silicon dioxide, chemically prepared
CAS: 5888-33-5	exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate
CAS: 40220-08-4	(2,4,6-trioxo-1,3,5-triazinane-1,3,5-triyl)triethylene triacrylate
CAS: 42978-66-5	tripropylene glycol diacrylate
CAS: 55818-57-0	4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid
CAS: 52408-84-1	glycerol, propoxylated, esters with acrylic acid
CAS: 13048-33-4	hexamethylene diacrylate
CAS: 15625-89-5	2,2-bis(acryloyloxymethyl)butyl acrylate
CAS: 128-37-0	Butylated hydroxytoluene
CAS: 1344-28-1	aluminium oxide
CAS: 4986-89-4	pentaerythritol tetraacrylate
CAS: 79-10-7	acrylic acid

(Contd. on page 10)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 9)

CAS: 97-88-1	n-butyl methacrylate
CAS: 150-76-5	mequinol
CAS: 80-62-6	methyl methacrylate

· TSCA new (21st Century Act) (Substances not listed)

CAS: 163702-01-0	Oligo[2-hydroxy-2-methyl-1-[4-(1-methylvinyl)phenyl]propanone]
CAS: 327622-75-3	Fatty acids, C18-unsatd., dimers, polymers with acrylic acid and 1,3,5-tris(2-hydroxyethyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione
CAS: 32435-46-4	bis(methacryloyloxyethyl) hydrogen phosphate
CAS: 954-16-5	2,4,6-trimethylbenzophenone
CAS: 157811-87-5	Siloxanes and silicones, di-Me, hydrogen-terminated, reaction products with pentaerythritol tetraacrylate

· Proposition 65

· Chemicals known to cause cancer:

CAS: 13463-67-7	titanium dioxide
-----------------	------------------

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

CAS: 7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
CAS: 80-62-6	methyl methacrylate	E, NL

· TLV (Threshold Limit Value established by ACGIH)

CAS: 13463-67-7	titanium dioxide	A4
CAS: 128-37-0	Butylated hydroxytoluene	A4
CAS: 1344-28-1	aluminium oxide	A4
CAS: 79-10-7	acrylic acid	A4
CAS: 80-62-6	methyl methacrylate	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 13463-67-7	titanium dioxide
-----------------	------------------

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

titanium dioxide
2-hydroxyethyl methacrylate
Oligo[2-hydroxy-2-methyl-1-[4-(1-methylvinyl)phenyl]propanone]
Dipentaerythritolhexaacrylat
2-phenoxyethyl acrylate

(Contd. on page 11)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 10)

tripropylene glycol diacrylate
4,4'-isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

glycerol, propoxylated, esters with acrylic acid
hexamethylene diacrylate

• **Hazard statements**

Combustible liquid.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.

• **Precautionary statements**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep container tightly closed.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing vapours.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection.
Use personal protective equipment as required.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing SDS:** Product safety department

• **Contact:** hse@printcolor.ch

• **Date of preparation / last revision** 01/08/2019 / 1

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 12)

Printing date 01/08/2019

Reviewed on 01/08/2019

Trade name: ST-White

(Contd. of page 11)

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2

US