

---

**SECTION 1) CHEMICAL PRODUCT AND SUPPLIER'S IDENTIFICATION**

---

**Product ID:** GS-020  
**Product Name:** Faster Accelerator  
**Revision Date:** 01/02/2019 **Date Printed:** 01/02/2019  
**Version:** 1.0 **Supersedes Date:** N.A.  
**Manufacturer's Name:** Deco Technology Group, Inc.  
**Address:** 1040 Segovia Cir, Placentia, CA 92870  
**Telephone:** (714) 639-3326  
**Fax:** (714) 639-2261  
**Emergency Phone:** Infotrac 800 535-5035  
**Product/Recommended Uses:** Paint related, nail care, industrial solvent with a wide variety of applications

---

**SECTION 2) HAZARDS IDENTIFICATION**

---

**Classification:**

Specific Target Organ Toxicity -Single Exposure (Narcotic Effects) - Category 3  
Aspiration Hazard - Category 2  
Skin Irritation - Category 3  
Eye Irritation - Category 2A  
Flammable Liquids - Category 1  
Acute toxicity Oral - Category 5  
Carcinogenicity – Category 2  
Reproductive Toxicity – Category 2  
Acute aquatic toxicity – Category 3  
Acute toxicity Dermal - Category 4  
Acute toxicity inhalation Vapor – Category 3

**Pictograms:**

**Signal Word:**  
Danger

**Hazardous Statements - Physical:**

Extremely flammable liquid and vapor

**Hazardous Statements - Health:**

May cause drowsiness or dizziness  
Maybe harmful if swallowed  
May be harmful if swallowed and enters airways  
Causes mild skin irritation  
Causes serious eye irritation

**Precautionary Statements - General:**

If medical advice is needed, have product container or label at hand.  
Keep out of reach of children.  
Read label before use.

**Precautionary Statements - Prevention:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take action to prevent static discharges.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Avoid breathing dust/fume/gas/mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Wash with soap and water thoroughly after handling.

**Precautionary Statements - Response:**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse with water or shower.  
In case of fire: Use DRY chemical, alcohol-resistant foam, water spray/fog or carbon-dioxide to extinguish.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER/doctor if you feel unwell.  
IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/attention.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.

**Precautionary Statements - Storage:**

Keep cool.  
Store in a well-ventilated place.  
Store in a well-ventilated place. Store locked up.  
Store locked up.

**Precautionary Statements - Disposal:**

Dispose of contents/container to disposal recycling center. Waste management should be in full compliance with federal, state and local laws.

---

**SECTION 3) COMPOSITION / INFORMATION ON INGREDIENTS**

---

| <b>CAS</b>   | <b>Chemical Name</b>   | <b>% by Weight</b> |
|--------------|------------------------|--------------------|
| 0000067-64-1 | ACETONE                | 20%                |
| 0000071-43-2 | BENZENE                | 0 - 0.001 %        |
| 0001330-20-7 | XYLENE                 | 70%                |
| 0000108-10-1 | METHYL ISOBUTYL KETONE | 10%                |

---

**SECTION 4) FIRST-AID MEASURES**

---

**Inhalation:**

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If victim is not breathing, call 911 and administer CPR as directed.

Eliminate all ignition sources if safe to do so.

**Skin Contact:**

Rinse/wash with lukewarm, gently flowing water (and mild soap) for 15-20 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention.

**Eye Contact:**

Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Get immediate medical attention.

**Ingestion:**

Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position. Immediately call 911 POISON CENTER/doctor/. Immediately transport to the nearest medical facility for treatment.

---

**SECTION 5) FIRE-FIGHTING MEASURES**

---

**Suitable Extinguishing Media:**

Dry chemical, foam, carbon dioxide or fog is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and

water on the same surface is to be avoided as water destroys the foam. Sand or earth may be used for small fires only.

**Unsuitable Extinguishing Media:**

No data available.

**Specific Hazards in Case of Fire:**

No data available.

**Fire-fighting Procedures:**

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**Special Protective Actions:**

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

---

**SECTION 6) ACCIDENTAL RELEASE MEASURES**

---

**Emergency Procedure:**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

RELEASE CAN CAUSE FIRE/EXPLOSION. LIQUIDS/VAPORS MAY IGNITE.

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

**Recommended Equipment:**

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

**Personal Precautions:**

Avoid breathing vapor. Avoid contact with skin, eye or clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use explosive proof equipment. Avoid inhalation of dust and contact with skin and eyes. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

**Environmental Precautions:**

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

**Methods and Materials for Containment and Cleaning up:**

Sand, clay and absorbent socks can be used to contain a spill.

---

**SECTION 7) HANDLING AND STORAGE**

---

**General:**

Wash hands after use.  
Do not get in eyes, on skin or on clothing.  
Do not breathe vapors or mists.  
Use good personal hygiene practices.  
Eating, drinking and smoking in work areas is prohibited.  
Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

**Ventilation Requirements:**

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

**Storage Room Requirements:**

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty container retain residue and may be dangerous. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.  
Ground and bond containers and receiving equipment. Avoid static electricity by grounding.  
Electrostatic charges may be generated during pumping. Keep away from aerosols, flammables, oxidizing agents, corrosives and from other flammable products.

---

**SECTION 8) EXPOSURE CONTROLS, PERSONAL PROTECTION**

---

**Respiratory Protection:**

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Select a filter suitable for organic gases and vapors meeting EN371.

### Skin Protection:

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

### Eye Protection:

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

### Appropriate Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

| Chemical Name          | OSHA TWA (ppm)     | OSHA TWA (mg/m3) | OSHA STEL (ppm)     | OSHA STEL (mg/m3) | OSHA Tables Z1,2,3 | OSHA Carcinogen | OSHA Skin designation | NIOSH TWA (ppm) | NIOSH TWA (mg/m3) | NIOSH STEL (ppm) | NIOSH STEL (mg/m3) | NIOSH Carcinogen |
|------------------------|--------------------|------------------|---------------------|-------------------|--------------------|-----------------|-----------------------|-----------------|-------------------|------------------|--------------------|------------------|
| ACETONE                | 1000               | 2400             |                     |                   | 1                  |                 |                       | 250             | 590               |                  |                    |                  |
| BENZENE                | 1 (a) / 25 ceiling |                  | 50(a) / 10 minutes. |                   | 1                  | 1               |                       | 0.1c            |                   | 1c               |                    | 1                |
| XYLENE                 | 100                | 435              |                     |                   |                    |                 |                       | 100             | 435               | 150              | 655                |                  |
| METHYL ISOBUTYL KETONE | 100                | 410              |                     |                   | 1                  |                 | 50                    | 205             | 75                | 300              |                    |                  |

| Chemical Name          | ACGIH TWA (ppm) | ACGIH TWA (mg/m3) | ACGIH STEL (ppm) | ACGIH STEL (mg/m3) | ACGIH Carcinogen | ACGIH Notations  | ACGIH TLV Basis                                  |
|------------------------|-----------------|-------------------|------------------|--------------------|------------------|------------------|--|
| ACETONE                | 500             | 1188              | 750              | 1782               | A4               | A4; BEI          | URT & eye irr;<br>CNS impair;<br>hematologic eff |
| BENZENE                | 0.5             | 1.6               | 2.5              | 8                  | A1               | SKIN; A1;<br>BEI | Leukemia   |
| XYLENE                 | 100             | 434               | 150              | 651                | A4               | A4; BEI          | URT & eye<br>Irr, CNS<br>imair                   |
| METHYL ISOBUTYL KETONE | 20              |                   | 75               | 307                | A3               | A3; BEI          | URT irr;<br>Dizziness<br>Headache                |

---

## SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

---

### Physical and Chemical Properties

|                    |                         |
|--------------------|-------------------------|
| Density            | 7.08 lb/gal             |
| % Solids By Weight | 0.00%                   |
| Density VOC        | 5.66# per Lb.           |
| % VOC              | 80%                     |
| VOC Actual         | 5.66# per gal. 675 G/L. |
| Specific Gravity   | 0.85                    |

---

|                                     |              |
|-------------------------------------|--------------|
| Appearance                          | Clear liquid |
| Odor Threshold                      | N/A          |
| Odor Description                    | Chacteristic |
| pH                                  | N/A          |
| Water Solubility                    | N/A          |
| Flammability Flashpoint below       | 73 °F        |
| Flash Point Symbol                  | N/A          |
| Flash Point                         | -40 °F       |
| Viscosity                           | N/A          |
| Lower Explosion Level               | N/A          |
| Upper Explosion Level               | N/A          |
| Vapor Pressure                      | N/A          |
| Vapor Density                       | N/A          |
| Freezing Point                      | N/A          |
| Melting Point                       | N/A          |
| Low Boiling Point                   | N/A          |
| High Boiling Point                  | N/A          |
| Auto Ignition Temp                  | N/A          |
| Decomposition Pt 0 Evaporation Rate | N/A          |
| Coefficient Water/Oil               | N/A          |

VOC Composite Partial Pressure

0.00279882 mmHg  
(Calculated @ 20 C/68 F)

---

## **SECTION 10) STABILITY AND REACTIVITY**

---

**Stability:**

Stable under normal conditions of use.

**Conditions to Avoid:**

Avoid heat, sparks, open flames and other ignition sources.

**Hazardous Reactions/Polymerization:**

No data available.

**Incompatible Materials:**

Strong oxidizing agents.

**Hazardous Decomposition Products:**

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

---

## **SECTION 11) TOXICOLOGICAL INFORMATION**

---

**Acute toxicity:**

Ingestion: May be harmful or fatal if swallowed.

**Skin Corrosion/Irritation:**

Causes mild skin irritation

**Serious eye damage/irritation:**

Causes serious eye irritation

**Germ cell mutagenicity:**

No data available

**Respiratory/Skin Sensitization:**

Slightly irritating to respiratory system.

**Carcinogenicity:**

No data available



**Reproductive toxicity:**

No data available

**Specific Target Organ Toxicity - Repeated Exposure:**

No data available

**Specific Target Organ Toxicity - Single Exposure:**

May cause drowsiness or dizziness

**Aspiration hazard:**

May be harmful if swallowed and enters airways

**0000067-64-1 ACETONE**

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m<sup>3</sup> (4-hour exposure) (29)

LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m<sup>3</sup> (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32, unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

**0000071-43-2 BENZENE**

LC50 (rat): 13,700 ppm (4 hour exposure) (26); 9,980 ppm (7 hour exposure) (13,200 ppm - equivalent 4 hour exposure) (18)

LD50 (oral, rat): 930 mg/kg (19); 5,600 mg/kg (2); 11.4 ml/kg (10,032 mg/kg) (21)

LD50 (oral, mouse): 4,700 mg/kg (11; unconfirmed)

LD50 (skin, rabbit and guinea pig): Greater than 9,400 mg/kg (20)

**0001330-20-7 XYLENE**

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethyl benzene) (1)

LC50 (rat): 6700 ppm (4-hour exposure) (65% m-Xylene, 7.6% o-Xylene, 7.8% p-xylene, 19.3% ethyl benzene) (2) ethyl benzene) (1) LC50 (rat): 6700 ppm (4-hour exposure) (65% m-Xylene, 7.6% o-Xylene, 7.8% p-Xylene, 19.3% ethyl benzene)(2)

LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1)

LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethyl benzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethyl benzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-Xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethyl benzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethyl benzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-Xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

**0000108-10-1 METHYL ISOBUTYL KETONE**

LC50 (rat): 2000 - 4000 ppm (4-hour exposure) (1)

LD50 (oral, rat): 2,080 mg/kg (1)

LD50 (oral, male mouse): 1,200 mg/kg; cited as 1.5 mL/kg (3)

LD50 (dermal, rabbit): greater than 3000 mg/kg (9)

**Chronic exposure**

**0001330-20-7 XYLENE**

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

**Potential Health Effects - Miscellaneous**

**0000067-64-1 ACETONE**

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, and skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

**0001330-20-7 XYLENE**

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, and lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

**0000108-10-1 METHYL ISOBUTYL KETONE**

The following medical conditions may be aggravated by exposure: asthma, respiratory disease, eye disorders, pulmonary conditions, skin disorders. Repeated or prolonged skin contact may cause any of the following: dryness, cracking of the skin, defatting. Inhalation may cause any of the following: dizziness, stupor (central nervous system depression), drowsiness, respiratory tract irritation.

---

**SECTION 12) ECOLOGICAL INFORMATION**

---

**Bio-accumulative Potential:**

No data available.

**Persistence and Degradability:**

No data available.

**Mobility in Soil:**

No data available.

**Toxicity:**

Harmful to aquatic life

**Other adverse effects:**

No data available.

**Bio-accumulative Potential**

**0000067-64-1**      **ACETONE**

Does not bioaccumulate

**Persistence and Degradability**

**0000067-64-1**      **ACETONE**

91% readily biodegradable, Method: OECD Test Guideline 301B

---

**SECTION 13) DISPOSAL CONSIDERATIONS**

---

**Waste Disposal Method:**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

---

**SECTION 14) TRANSPORT INFORMATION**

---

**U.S. DOT Information:**

UN1090, Acetone, 3, PG II  
UN1307, Xylenes, 3, PG II  
UN1245, Methyl Isobutyl Ketone, 3, PG II

**Emergency Response Guide (ERG):**

---

**SECTION 15) REGULATORY INFORMATION**

---

| CAS              | Chemical Name                | % By Weight           | Regulation List   |
|------------------|------------------------------|-----------------------|---|
| 000006<br>7-64-1 | ACETONE                      | 98.000% -<br>100.000% | CERCLA,SARA312,VOC_exempt,TSCA,RCRA,OSHA  |
| 0000071-<br>43-2 | BENZENE                      | 0.005%                | CERCLA,SARA312,SARA313,VOC,IARC Carcinogen,TSCA,RCRA, OSHA Carcinogen,CA_TAC_TOX,CA_TAC_Carcinogen,CA_Carcinogen,NEI - National Emissions Inventory, CA_Prop65 - California Proposition 65, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer,CA_Prop65_Type_Toxicity_Develop - CA_Proposition65_Type_Toxicity_Developmental,CA_Prop65_Type_Toxicity_Male - CA_Proposition65_Type_Toxicity_Male,OSHA |
| 0001330-<br>20-7 | XYLENE                       | 78.079% -<br>81.266%  | CERCLA,SARA312,SARA313,VOC,IARCCarcinogen,TSCA,RCRA,C A_TAC_TOX,NEI - National Emissions Inventory,OSHA   |
| 0000108-<br>10-1 | METHYL<br>ISOBUTYL<br>KETONE | 98.000% -<br>100.000% | CERCLA,SARA312,SARA313,VOC,TSCA,RCRA,CA_TAC_TOX,C A_Carcinogen,NEI - National Emissions Inventory,CA_Prop65 - California Proposition 65,CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer,CA_Prop65_Type_Toxicity_Develop - CA_Proposition65_Type_Toxicity_Developmental,OSHA  |

---

**SECTION 16) OTHER INFORMATION**

---

**General:**

Deco Technology Group, Inc. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. It is the Buyer's/User's responsibility to ensure that his activities comply with all Federal, State, Provincial or Local laws. The information presented here pertains only to the product as shipped. The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. NO warranty or guarantee is expressed or implied regarding the accuracy of this data or the results to be obtained from the use of the product.

**HMIS**

|                            |   |
|----------------------------|---|
| <b>HEALTH</b>              | 3 |
| <b>FLAMMABLE</b>           | 3 |
| <b>REACTIVE</b>            | 0 |
| <b>PERSONAL PROTECTION</b> | H |

---

## **DISCLAIMER**

To the best of our knowledge, the information contained herein is accurate. However, neither Deco Technology Group, Inc. nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.